

LS-224HB

PIR High Bay Sensor Switch is a high performance motion sensor design to cater High / Low bay application areas with ceiling height upto 12m.

Features

Precision detection

Analog and Digital signal processing is combined to remove noise and hence to reduce false switching with **SpotOn** filter algorithm in multiple domains including amplitude, frequency, pulse count with bipolar signal processing.

Uniform sensitivity optic

Optimum detection is achieved by using uniform zone distribution optic / lens manufactured using patented material for uniform sensitivity throughout detection area

Environmental adoption

ZANSA sensor monitors changes in environmental temperature condition and adjust the sensing parameters for revolutionary performance.

Manual override on Operational modes

Operating mode can be overridden by switching power switch itself

Quick installation mode

A unique feature to help installation professional to quickly analyse sensor performance in required detection area

Versatile performance:

Advance detection technology and compact design make the sensors ideal for both residential and commercial applications.

Universal Mounting Design

Swivel ball joint bracket helps in directing sensor towards required detection area even for 360° ceiling mount sensor on Wall, Corner and ceiling in suspended fashion apart from traditional surface mounting.

Sleek, attractive housing

The sleek housing fits into variety of building styles and blends with any room decor. The housing offers detachable connector or separate cable for easy, fast and trouble free installation



**PIR
HIGH-BAY
SWITCH**



ZANSA™

LS-224HB

Specifications:

Physical Dimensions (mm)

(H x W x D)
100 x 42 x 75

Weight

Packed Product: approx. 160gm

Power requirements:

230VAC \pm 10%, 40mA.

Load

1500W Incandescent
360W Fluorescent.

Detection range:

360° x 24m at 25°C

Mounting Height:

12.2m typical

Temperature compensation

Automatic bidirectional temperature compensation

Operational modes

ON: Output is always ON

OFF: Output is always OFF

Auto: Output will be switched on and off depending on valid PIR signal

Protections

Short circuit protection

Surge Protection

EMI/RFI Protection

Harmonic Filter

Relay Contact Protection

ON Time

Determines the lamp on time after last motion is detected. Different 'ON Time' can be selected by placing jumper head at following pin code.

- 30S: 30 Seconds.
- 1M: 1 minute
- 3M: 3 minute
- 5M: 5minute
- 7.30M: 7.30 minute
- 10M: 10 minute
- 15M: 15 minute
- 20M: 20 minute

Lux level

Determines the operation of light switch, by sensing ambient light. Different lux levels can be selected by setting proper jumper at following pin code.

- N: Night mode (1 - 3 LUX)
- U: Dusk mode (4 - 10 LUX)
- X: Reserved for future use
- D: Day mode (24 hrs)

Sensitivity

1-2 steps within the field of view

- L: Minimum sensitivity.
- M: Medium sensitivity.
- H: Maximum sensitivity.


**PIR
HIGH-BAY
SWITCH**



ZANSA™

LS-224HB

Detection Pattern



**PIR
HIGH-BAY
SWITCH**

Ordering

Part Number
LS-224HB

Description
PIR High Bay Switch

eConzerv Solutions Pvt. Ltd.
Plot no 25, Survey No. 17/8/24,
Shivnery Park, Balewadi, Pune - 411 045,
Maharashtra, India.
Tele: +91-20-2588 4920, 6530 3130, 9420068913.
URL: www.econzerv.com
email: customercare@econzerv.com

